

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
<b>Automotive Articles</b>																			Automotive	external	
Auto-Nachspühl -Polish														X					15 - 25	Automotive	external
Bicycle-SET TT																X			15 - 25	Automotive	external
Bike- „Tyre sealant spray“, 75 ml														X					15 - 25	Automotive	external
Bike Cleaner														X					15 - 25	Automotive	external
Bike wax spray														X					15 - 25	Automotive	external
Briliant gloss spray														X					15 - 25	Automotive	external
CAMPLAST Cement																X			15 - 25	Automotive	external
CAMPLAST repair patch																X			15 - 25	Automotive	external
CAMPLAST SET																X			15 - 25	Automotive	external
Chain Cleaner														X					15 - 25	Automotive	external
Chain Cleaner spray														X					15 - 25	Automotive	external
Chain spray														X					15 - 25	Automotive	external
Cleaning agent R4																	X		15 - 25	Automotive	external
Cleaning agent R4, free of chlorinated and aromatic hydrocarbons																	X		15 - 25	Automotive	external
Cleaning rubber for Extruder											X								15 - 25	Automotive	external
CLEAN-UP														X					15 - 25	Automotive	external
Cockpit care														X					15 - 25	Automotive	external
Cockpit cleaner														X					15 - 25	Automotive	external
Cream soap														X					15 - 25	Automotive	external
E-Line Diagonal																	X		15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
Easy Repair Gum											X								15 - 25	Automotive	external
Emergency Repair Kit														X					15 - 25	Automotive	external
Envelope repair patches													X						15 - 25	Automotive	external
Fast Dry Cement BL																X			15 - 25	Automotive	external
Firehose-pressure tube-patches														X					15 - 25	Automotive	external
Foam wash														X					15 - 25	Automotive	external
Hand Cleaner SOFT														X					15 - 25	Automotive	external
Hand Cleaner SUPER														X					15 - 25	Automotive	external
Hand Cleaner TOP CLEAN														X					15 - 25	Automotive	external
HD-High-pressure powder cleaner														X					15 - 25	Automotive	external
HD-Shampoo														X					15 - 25	Automotive	external
High-gloss foam wash														X					15 - 25	Automotive	external
HR SOLUTION, free of chlorinated and aromatic hydrocarbons																X			15 - 25	Automotive	external
Icefree / Oil														X					15 - 25	Automotive	external
INNERLINER SEALER												X							15 - 25	Automotive	external
INNERLINER SEALER, sprayable												X							15 - 25	Automotive	external
Insect remover														X					15 - 25	Automotive	external
LIQUID BUFFER																	X		15 - 25	Automotive	external
LIQUID BUFFER Spray														X					15 - 25	Automotive	external
Maintenance oil														X					15 - 25	Automotive	external
MINICOMBI, A,3, A4,5, A6, B8, B10																	X		15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
MTC – X PN/RAD patches											X								15 - 25	Automotive	external
MTR RUBBER											X								15 - 25	Automotive	external
MTR RUBBER, robe for Extruder											X								15 - 25	Automotive	external
MTR SOLUTION, free of chlorinated and aromatic hydrocarbons											X								15 - 25	Automotive	external
MTR SUPER FINISH RUBBER											X								15 - 25	Automotive	external
MTR-CR RUBBER											X								15 - 25	Automotive	external
Multi-purpose cold cleaner														X					15 - 25	Automotive	external
NANO-Ketting pray														X					15 - 25	Automotive	external
Perfekt cleaner														X					15 - 25	Automotive	external
Plastic cleaner														X					15 - 25	Automotive	external
PN repair patches																	X		15 - 25	Automotive	external
PN repair patches-OTR																	X		15 - 25	Automotive	external
PROFI-MINICOMBI-BOX												X							15 - 25	Automotive	external
RAD, Series 100																	X		15 - 25	Automotive	external
RAD, Series 500																	X		15 - 25	Automotive	external
RADIAL ANCHOR SEAL																X			15 - 25	Automotive	external
E-Line RADIAL																	X		15 - 25	Automotive	external
Release agent SHE-100														X					15 - 25	Automotive	external
REMA STEM 6 / 8 / 10 / 12																	X		15 - 25	Automotive	external
REMAXX "SPORT"														X					15 - 25	Automotive	external
REMAXX ANTI-GLISS-Lube														X					15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
REMAXX BEAD SEALER														X					15 - 25	Automotive	external
REMAXX BLACK														X					15 - 25	Automotive	external
REMAXX CRÈME-W														X					15 - 25	Automotive	external
REMAXX CRÈME-W-EM														X					15 - 25	Automotive	external
REMAXX Demounting Fluid														X					15 - 25	Automotive	external
REMAXX Fluid														X					15 - 25	Automotive	external
REMAXX Fluid Spray														X					15 - 25	Automotive	external
REMAXX Lube Liquid														X					15 - 25	Automotive	external
REMAXX LUBRICANT-SE For mounting solid tyres														X					15 - 25	Automotive	external
REMAXX MONT 2000														X					15 - 25	Automotive	external
REMAXX MONTSEAL														X					15 - 25	Automotive	external
REMAXX TRUCK														X					15 - 25	Automotive	external
REMAXX UNIVERSAL														X					15 - 25	Automotive	external
REMAXX WAX-H														X					15 - 25	Automotive	external
Rep & Air motor bike																X			15 - 25	Automotive	external
Rep & Air motorbike, tublesse																X			15 - 25	Automotive	external
REPVULC Patch MTC PN																X			15 - 25	Automotive	external
REPVULC Patch MTC RAD																X			15 - 25	Automotive	external
REPVULC Patch MTC X PN											X								15 - 25	Automotive	external
REPVULC Patch MTC X RAD											X								15 - 25	Automotive	external
RetreadLube								X											15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
Rim Cleaner														X					15 - 25	Automotive	external
Rubber base valves																	X		15 - 25	Automotive	external
Rubber base valves (Hot Cure)											X								15 - 25	Automotive	external
RUN FLAT Repair-SET																X			15 - 25	Automotive	external
SEALASTIC																X			15 - 25	Automotive	external
SEALFIX														X					15 - 25	Automotive	external
Seam seam sealing compound														X					15 - 25	Automotive	external
SELASTIC KIT																X			15 - 25	Automotive	external
Silicon spray														X					15 - 25	Automotive	external
SILK SKIN														X					15 - 25	Automotive	external
SKIN PROTECT														X					15 - 25	Automotive	external
Special Bike Fluid														X					15 - 25	Automotive	external
SPECIAL CEMENT BL																X			15 - 25	Automotive	external
SPECIAL CEMENT BL, free of chlorinated and aromatic hydrocarbons																X			15 - 25	Automotive	external
SPECIAL CEMENT OTR																X			15 - 25	Automotive	external
Special Cleaning Solvent																	X		15 - 25	Automotive	external
SUPER RADIAL ANCHOR SEAL																X			15 - 25	Automotive	external
SUPER SELASTIC																X			15 - 25	Automotive	external
SUPER SELASTIC KIT																X			15 - 25	Automotive	external
SV BLUE BONDING RUBBER blue														X					15 - 25	Automotive	external
T2-Compound A + B											X								15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
T2-Solution A + B											X								15 - 25	Automotive	external
T2- Cleaning Rubber														X					5 - 25	Automotive	external
T2-Solution A + B, free of chlorinated and aromatic hydrocarbons											X								15 - 25	Automotive	external
Talcum																	X		15 - 25	Automotive	external
Thermopress MTR cushion gum											X								15 - 25	Automotive	external
Thermopress patches												X							15 - 25	Automotive	external
TT SEAL														X					15 - 25	Automotive	external
TT SEAL XXL														X					15 - 25	Automotive	external
Tube Patch, black																	X		15 - 25	Automotive	external
Tube Patch, red																	X		15 - 25	Automotive	external
TUBELESS-Repair-SET																X			15 - 25	Automotive	external
TUBE-Repair-SET																X			15 - 25	Automotive	external
Tyre Color														X					15 - 25	Automotive	external
TYRE COMPOUND																	X		15 - 25	Automotive	external
Tyre-Repair-SET											X								15 - 25	Automotive	external
UNIVERSAL PATCH / UP 3 / 4,5 / 6 / 8 / 10 / 12																	X		15 - 25	Automotive	external
Universal-Flick-Box														X					15 - 25	Automotive	external
Valves with rubber-patch																	X		15 - 25	Automotive	external
Valves with rubber-patch																	X		15 - 25	Automotive	external
Valves with rubber-patch (Hot vulcanization)																		X	15 - 25	Automotive	external
Valve Patch																	X		15 - 25	Automotive	external

## Shelf Life from the time of manufacture



REMA TIP TOP Industrial and Automotive Products

Storage conditions: As specified in column "storage temperature" in original (sealed) packaging.

Autor: Dep. tq  
Index B/ Stand: 10.03.2014

Product	2 weeks	1 month	2 months	2,5 months	3 months	4 months	5 months	6 months	8 months	9 months	1 year	1,25 years	1,5 years	2 years	3 years	4 years	5 years	10 years	Storage Temperature in °C	Industry / Automotive	internal / external
Valve patch with fabric reinforced																X			15 - 25	Automotive	external
VULC Compound A + B												X							15 - 25	Automotive	external
VULC Compound A + B Set											X								15 - 25	Automotive	external
VULC Compound A + B, free of chlorinated and aromatic hydrocarbons											X								15 - 25	Automotive	external
SVS-Vulc																X			15 - 25	Automotive	external
Windscreen cleaner														X					15 - 25	Automotive	external

Above data is based on extensive tests and is to be considered only as guideline without any obligation. As we are continuously developing and improving our products, we recommend to consider the date of this data sheet and, if necessary, to ask if there have been changes in the meantime. In case of further questions please contact one of our technical advisors for detailed information at:

REMA TIP TOP AG  
Business Segments Material Processing and Automotive  
Gruber Strasse 63, 85586 Poing/Germany  
Telefon: +49 8121 707-10245/ -10270  
Telefax: +49 8121 707-10222  
info@tiptop.de  
www.rema-tiptop.com